HIGHLINE MFG.

BALE MOVER 700

'98

Assembly-Operator Parts Manual

Memo

To:

All Departments

From:

Shane Tulik

CC:

Mario Piche

Date:

12/23/98

Re:

Manitoba Highways and Transportation - Lighting and Marking

As discussed previously, legislation was passed in Manitoba requiring lighting and marking on all agricultural equipment. This legislation applies to all equipment manufactured on or after January 1, 1998 and must be adhered to for all machines sold into Manitoba. The following Highline machines are affected by this legislation:

- 1. 500BM Balemover.
- 2 7008M Balemover
- 3 1400BM Balemover
 - 4. Balepro Hitch
 - 5 Topgun
 - 6. BP6800 Baleprocessor
 - 7. BP7800 Baleprocessor
 - 8. XL6084 Rockpicker
 - 9. XL78 Rockpicker.

I would like to again express the need to address this situation immediately by supplying either the dealers or the end user with the required lighting and marking in order to meet the Manitoba legislation. The details of supplying the safety kits will be shared by the sales, production, and customer service departments. These measures will supply the equipment owners with the necessary safety equipment and will allow us to retroactively meet and exceed the required legislation by following ASAE S279.10. The following light kits can be found in CMS:

Model	Light Kit Part No.	Other Requirements
500BM Balemover	40164	reflectors
7000M Belancies	40164	twinciors
1400BM Balemover	40169	reflectors
Balepro Hitch	Same requirement as BM	reflectors
Topgun	48089	reflectors
BP6800 Baleprocessor	48101	reflectors
BP7800 Baleprocessor	48103	reflectors
XL78 Rockpicker	To be completed	reflectors
XL6064 Rockpicker	To be completed	reflectors

HIGHLINE WARRANTY IS **INVALID** IF THE WARRANTY REGISTRATION FORM IS NOT SIGNED AND RETURNED

THE WARRANTY REGISTRATION FORM IS ENCLOSED WITH THE MANUAL

PLEASE COMPLETE AND MAIL WHEN UNIT IS SOLD

Table of Contents

Table of	of Contents	1
	Warranty	3
Preside	ents Message	5
Safety	Precautions	5
1.0	Pre-delivery & Installation Instructions	7
	1.1General Description of 700 Bale Mover	7
	1.2Pre-Delivery Check List	7
2.0	Operating Instructions	8
	2.1Pre-start instructions	8
	2.3Transporting Instructions	8
	2.4Bale Size Adjustment	8
	2.5Field Instructions	9
3.0	Maintenance Instructions	10
	Grease Locations	10
4.0	Parts Information	12
	4.1Tandem	12
	4.2Subframe	14
	4.3Hitch	
	4.4Rail and Crossmember Subframe	18
	4.5Forks	
	4.6Chain Tightner and Chain	22
	4.7Castor Wheel	
	4.8Castor Wheel Support	26
5.0	Hydraulics	28
	5.1Motor Hydraulies	28
	5.2Cylinder Hydraulics	30
6.0	Cylinders	
	6.1 3 x 8, 1 1/4 Rod	33
	6.2 3 X 10, 1 1/4 Rod	
	6.3 3 1/2 x 16, 1 1/2 Rod	
7.0	Hub	
	7.1Tandem Wheel	
	7.2Castor Wheel	41
8.0	Electrical	
	8.1Electrical Scematic	
	8.2Control Box and Wiring Harness	
9.0	Specifications	48

HIGHLINE Manufacturing Page 3

Warranty

HIGHLINE Mfg. Inc. warrants its products to the original owner for a period of two years from date of purchase, subject to the following provisions:

•1st year Warranty covers Parts & Labor

•2nd year Warranty covers Parts Only

- Warranty registration must be submitted to HIGHLINE Mfg. Inc. within 30 days of purchase.
- Highline Mfg Inc. is not liable for any damages to this equipment resulting from use of this
 equipment that is inconsistent with this manual and such is not covered under this warranty.
- Warranty will be void, and Highline Mfg. Inc.will not be liable in any way, if the equipment is used for any other purpose then the intended agricultural application.
- All warranty service must be handled through an authorized HIGHLINE Mfg. Inc.dealer. At
 the time of requesting warranty service, the purchaser must present evidence of the delivery
 date of the equipment. The purchaser shall pay any premium for requested overtime, any
 charge for making service calls, and any charges incurred in transporting the equipment to
 and from the location of the warranty service. Freight costs associated with warranty repairs
 are not reimbursable.
- Any labor subject to warranty must be authorized by a HIGHLINE Mfg. Inc. Representative, before work is started.
- Warranty will be void if any component of this equipment is altered or modified in any way, unless written permission is given by HIGHLINE Mfg. Inc.
- Equipment used for rental, custom work, industrial or construction use will not be warranted by Highline Mfg. Inc.
- HIGHLINE Mfg. Inc. will not assume any responsibility for any damage occurring to equipment which this equipment may be attached.
- Warranty terms and conditions are subject to provincial and state legislation.
- Warranty is limited to the Purchase price paid for the equipment, up to the Manufacturers suggested retail price. ANY LIABILITY RESULTING FROM THE WORKMANSHIP OF THIS EQUIPMENT is limited to the purchased price paid. Highline Mfg. Inc. assumes no responsibility whatsoever for liability resulting from the misuse or improper operation and maintenance of this equipment.

HIGHLINE Manufacturing Page 5

President's Message

The 700 Bale Mover, a proven name in the bale handling field is manufactured by

HIGHLINE Mfg Inc. The 700 Bale Mover was designed to work in the most difficult of bale

handling situations. A little time and effort spent in proper maintenance will assure the

performance and durability of your bale mover.

This operator manual has been prepared to provide information necessary for the safe and

efficient operation of your bale mover. In it you will find safety procedures, maintenance

routines and detailed parts diagrams.

In order to maintain high standards, changes or improvements are made from time to

time. HIGHLINE Mfg Inc. reserves the right to make those changes and add improvements

when practical to do so without incurring any obligation to make such changes and

improvements on machines sold previously.

Should the need arise, this manual will assist you in acquiring replacement parts. Should

your dealer not have the parts you require in stock, the dealer will be happy to order them for

you. If you should find that you require information not covered in this manual, feel free to

consult **HIGHLINE Mfg Inc.** or your local dealer.

HIGHLINE Mfg Inc. thanks and congratulates you for selecting a 700 Bale Mover as

the machine for your bale handling needs.

Raymond Bussiere

Ray & Busselle

President

Safety Precautions

CAREFUL OPERATION IS THE BEST INSURANCE AGAINST AN ACCIDENT

- Always disengage PTO and hydraulic motors before dismounting tractor.
- Keep yourself and others clear of rotating parts to prevent injury.
- Never allow anyone to stand near the bale mover while loading or unloading bales.
- Never attempt to manually remove bales from rails while hydraulic motors are engaged. Disconnect hydraulic motors before cleaning the bale mover.
- Remove transport locks before lowering forks. To remove transport locks, raise forks to slacken transport chain and remove transport pin. DO NOT lower forks when transport locks are in position otherwise sever damage WILL occur.
- Relieve pressure in hydraulic lines before disconnecting lines or performing maintenance on the hydraulic system.

1.0 Pre-Delivery & Installation Instructions

1.1 General Description of 700 Bale Mover

The 700 Bale Mover is 8' wide and a length of 41'7". One set of hydraulic lines is required for engaging hydraulic motors, and one set of hydraulic lines is required for operation of forks and deck cylinder. The 700 Bale Mover may either load or unload bales for easy transport and organization of bales.

1.2 Pre-Delivery Check List

Enclosed is a list of parts required if the 700 Bale Mover has not been assembled prior to delivery. If any parts are not included contact your authorized Highline dealer or **HIGHLINE Mfg Inc.**

2.0 Operating Instructions

2.1 Pre-Start Instructions

Transport chains need to be removed before operation of the forks. To remove transport chains, raise forks slightly and remove transport pins. DO NOT lower forks when transport chains are in position otherwise severe damage WILL occur.



Figure 1. Locks in Transport Position

2.3 Transporting Instructions

To ensure safe transport of the 700 Bale Mover, forks should be in the transport position with the transport chains in place. To put transport chains in place, raise the forks until the transport pin can be put in place safely. Lower forks to take the slack up in the transport chains.

2.4 Bale Size Adjustment

The bale size is adjustable through the fork adjusting plate. By moving the forks (Figure 2) to adjust for the correct size of bale.




Figure 2. Fork Adjusting

HIGHLINE Mfg. Inc.

2.5 Field Instructions

For proper operation, the 700 Bale Mover should run at a field speed of 3-4 mph (4.8-6.5 km/h). When picking bales, a full stop is not required. Bales are picked and placed on the bed continuously by lifting the bale into position and moving the preceding bales back to fit the new bale on.

3.0 Maintenance Instructions

To ensure long operating life of your 700 Bale Mover, follow this maintenance procedure.

- Periodically check tire air pressure to maintain equal tire pressure. The operating tire pressure should be 90 psi
- · Periodically check all bolts for tightness.
- Periodically check chain tightner. The chain should appear to be 2 inches off the bottom of the rail
- Grease the following points as described.

Grease Locations



Grease No	Description	Frequency
1	Arm, Pivot, Right	Daily

Figure 3. Pivot Arm Grease Location

-	·		
1. 3		. سندانو	The state of the s
		1	
PARTERIA			

Grease No	Description	Frequency
2	Arm, Slide, Pivot, Right	Daily

Figure 4. Pivot Slide Arm Grease Location

HIGHLINE Mfg. Inc.




Figure 5. Oscillating Tandem Grease Location

Grease No	Description	Frequency
3	Pocket, Beam Walking, Left,	Weekly
4	Pocket, Beam Walking, Right	Weekly
5	Pocket, Beam Walking, Middle	Weekly




Figure 6. Rear Sprocket Pin


Grease No	Description	Frequency
6	Pin, Sprocket, Rear, Left,	Daily
7	Pin, Sprocket, Rear, Right,	Daily

4.0 Parts Information

4.1 Tandem


Item	Part No.	Description	Quantity
1	30102	Hub, 8 Bolt, 5000 lbs, EM5500	4
2	30207	Zerk, Grease, 1/4-28	2
3	40108	Beam, Walking, Main	2
4	40122	Assembly, Wheel, Complete	4
5	91061	Bolt, Wheel, 9/16"	32
6	31270	UALE STEAT	

Part No. Description
30100 Tire, 11L-15FI, 12 Ply
30104 Rim, 15 x 8 x 8, 1.5 Off, 6000#



4.2 Subframe

Item	Part No.	Description	Quantity
1		Assembled Tandems	2
2	40139	Subframe, 7BM (1997)	1
3	45006	Pocket, Beam, Walking, Middle	1
4	B5C1028P	Bolt, 5/8" x 1 3/4", Pltd.	14
5	LNC08	Nut, Nylock, 5/8"	14



HIGHLINE Mfg. Inc.


4.3 Hitch

Item	Part No.	Description	Quantity
1	40003	Pin, Hitch, Subframe	2
2	45010	Hitch, A-Frame, Left	1
3	45011	Hitch, A-Frame, Right	1
4	40490	Crossmember, Hitch	1
5	45060	Hitch, Tongue, Double	1
6	92095	Jack, Sidewind, 5000 lbs x 15"	1
7	B5C16120P	Bolt, 1" x 7 1/2", Pltd	2
8	B5C0824P	Bolt, 1/2" x 1 1/2", Pltd.	8
9	LNC16	Nut, Nylock, 1"	2
10	LNC10	Nut, Nylock, 1/2"	8
11	CP440	Cotterpin, 1/4" x 2 1/2"	2

Page 16

NOTE: Place hitch crossmember in place leaving bolts loose.

Insert double tongue hitch and tighten making sure angles are flush.




4.4 Rail and Crossmember Subframe

Item	Part No.	Description	Quantity
1	40085	Arm, Divider, Bale	2
2	40140	Bracket, Cylinder	1
3	40134	Rail, Left, 7BM	1
4	40135	Rail, Right, 7BM	1
5	45016	Divider, Bale	1
6	45022	Bracket, Sign, SMV	1
7	45130	Crossmember, Widened	1
8	30206	Holder, Hose, Hydraulic, 1/2"	1
9	92028	Sign, Vehicle, Moving, Slow	1
10	92061	Bumper, Rubber	1
11	B5C1028P	Bolt, 5/8" x 1 3/4", Pltd.	6
12	B5C0824P	Bolt, 1/2" x 1 1/2", Pltd.	58
13	B5C0412P	Bolt, 1/4" x 3/4", Pltd.	2
14	LNC08	Nut, Nylock, 5/8"	6
15	LNC08	Nut, Nylock, 1/2"	61
16	LNC04	Nut, Nylock, 1/4"	2
17	FW08	Washer, Flat, 1/2", Pltd	1

Note: Install all rails on subframe leaving bolts loose.


Install deck cylinder in the fully closed position between the hitch and deck lug. Lift hitch until front of the bale mover is fully supported then tighten all bolts.



HIGHLINE Mfg. Inc.

4.5 Forks

Item	Part No.	Description	Quantity
1	40008	Pin, Arm, Pivot	2
2	40010	Pin, Arm, Side, Pivot	1
3	40012	Arm, Pivot, Right	1
4	40149	Arm, Slide, Pivot, Right	1
5	40019	Pin, Lock, Safety	1
6	40151	Fork, Right	1
7	40152	Fork, Right, 1/4 Turn	1
8	30207	Zerk, Grease, 1/4-28	2
9	30217	Chain, Transport, Bale Mover	1
10	91608	Hairpin, 1/8" x 2 1/2"	1
11	BFC1248P	Bolt, 3/4" x 3", Pltd.	4
12	B5C1032P	Bolt, 5/8" x 2", Pltd.	1
13	B5C1024P	Bolt, 5/8" x 1 1/2", Pltd	8
14	LNC12	Nut, Nylock, 3/4"	4
15	LNC10	Nut, Nylock, 5/8"	13
16	CP0440	Cotterpin, 1/4" x 2 1/2"	3
Not Shown	40088	Bumper, Front	1
Not Shown	40118	Front Bumper Mount	2
Not Shown	30269	5/8 x 6 x 4-3/8 U Bolt	2
16	CP0440	Cotterpin, 1/4" x 2 1/2"	3



4.6 Chain Tightner and Chain


Item	Part No.	Description	Quantity
1	40115	Slide, Mount, Motor, Left	1
2	40116	Slide, Mount, Motor, Right	1
3	40121	Pin, Sprocket, Rear	2
4	30197	Pin, Roll, 3/16" x 1 1/2"	2
5	30207	Zerk, Grease, 1/4"-28	2
6	91508	C2062H X 304PI CHAIN	4
7	91510	Link, Connecting, C2062	2
	91511	Link, Offset, C2062	1
9	92023	Sprocket, Rear	2
10	92024	Bushing, Brass	2
11	NRHACME16	Nut, Acme, 1" – 5 RH	4
12	LW16P	Washer, Lock, 1", Pltd.	2
	91517	C2062h Chain per foot	N/A

Note:

Chain is fed from the front of the machine.


This is accomplished by feeding a piece of wire from the front through the tube and pulling the chain through.

This can be accomplished by one person, but two people would make the operation easier.




4.7 Castor Wheel

Item	Part No.	Description	Quantity
1	E2852	Holder, Pivot, Wheel, Land	1
2	E2853	Holder, Wheel, Land	1
3	E3060	Bushing, Wheel, Castor	1
4	E3075	Bushing, Wheel, Castor	1
5	70063	Fork, Wheel, Land	1
6	91031	Tire, Castor, c/w Rim, 4-Bolt	1
7	91060	Bolt, Wheel, 1/2"	4
8	91073	Hub, Castor, 4-Bolt, Complete	1
9	B5C16144P	Bolt, 1" x 9", Pltd.	1
10	B5C0440P	Bolt, 1/4" x 2 1/2", Pltd	1
11	LNC16	Nut, Nylock, 1"	1
12	LNC04	Nut, Nylock, 1/4"	1



4.8 Castor Wheel Support


Item	Part No.	Description	Quantity
1	40117	Wheel, Castor	1
2	40136	Arm, Support	1
3	45025	Pin, Wheel, Support	1
4	30207	Zerk, Grease, 1/4"-28	1
5	CP0440P	Cotterpin, 1/4" x 2 1/2"	1



5.0 Hydraulics

5.1 Motor Hydraulics

Item	Part No.	Description	Quantity
1	30204	Fitting, Hyd, 10MB-8MJ	2
2	30205	Hose, 1/2" x 57", 8FJ90TL	1
3	30209	Tip, Male, Pioneer, 1/2"	2
4	40077	Washer, Motor, 1 1/4" ID x 1 7/8" OD	2
5	92063	Sprocket, Motor	2
6	92184	Motor, Hydraulic	2
7	90310	Hose, 1/2" x 96", 10MBX-8MP	2
8	B5C0844P	Bolt, 1/2" x 2 3/4", Pltd.	8
9	LNC08	Nut, Nylock, 1/2"	8
10	FW10P	Washer, Flat, 5/8", Pltd.	2
11	FW08P	Washer, Flat, 1/2", Pltd.	8




5.2 Cylinder Hydraulics

Item	Part No.	Description	Quantity
1	E4726	Tee, Double, Hydraulic	1
2	30198	Hose, 3/8" x 18", 6FJX-6MP	1
3	30199	Hose, 3/8" x 18", 6MP-8MPX	1
4	30200	Fitting, Plug, 8MB	3
5	30201	Hose, 3/8" x 44", 8FJX-6MP	1
6	30202	Fitting, Hyd, 6MP-8MJ90	1
7	30203	Fitting, Hyd, 4MP-6MJ90	1
8	30209	Tip, Male, Pioneer, 1/2"	2
9	30210	Clamp, Line, Oil	4
10	30211	Fitting, 8MB-8MJ90	3
11	30153	Fitting, 8MP-8MJ90	5
12	30313	Fitting, 8MJT	1
13	90117	Cylinder, 3" x 8", 1 1/4" Rod	1
14	90118	Cylinder, 3" x 10", 1 1/4" Rod	1
15	90120	Cylinder, 3 1/2" x 13", 1 1/2" Rod	1
16	90272	Hose, 3/8" x 24", 8FJX-8FJX	1
17	90301	Hose, 3/8" x 120", 8MP-8FJX	2
18	90305	Hose, 3/8" x 30 1/2", 6MP-8FJX	2
19	90308	Hose, 3/8" x 50", 8FJX -6MP	1
20	90313	Hose, 3/8" x 18", 8FJX-8FJX	2
21	90691	Valve, Check, Pilot, PC-50	1
22	92089	Valve	1
23	LNC06	Nut, Nylock, 3/8"	2
24	LNC05	Nut, Nylock, 5/16"	2
25	LNC04	Nut, Nylock, 1/4"	2
26	FW05P	Washer, Flat, 5/16", Pltd.	2

5.2 Cylinder Hydraulics

Item	Part No.	Description	Quantity
1	E4726	Tee, Double, Hydraulic	1
2	31269	Hose, 3/8" x 42-1/2", 8FJX-6MP	2
3	32055	Hose, 3/8" x 19", 6MP-8FJX	1
4	30200	Fitting, Plug, 8MB	3
5	30201	Hose, 3/8" x 44", 8FJX-6MP	1
6	32954	Hose, Hyd, 3/8 x 16, 6MP-6FJX	1
7	32641	Fitting, Hyd, 4MB-6MJ 6MB-6M5	1
8	30209	Tip, Male, Pioneer, 1/2"	2
9	30210	Clamp, Line, Oil	4
10	30211	Fitting, 8MB-8MJ90	4
11	30212	Fitting, 8MP-8MJ90	6
12	30313	Fitting, 8MJT	1
13	90117	Cylinder, 3" x 8", 1 1/4" Rod	1
14	90118	Cylinder, 3" x 10", 1 1/4" Rod	1
15	90120	Cylinder, 3 1/2" x 13", 1 1/2" Rod	1
16	32963	Hose, 3/8" x 15", 8FJX	1
17	90301	Hose, 3/8" x 120", 8MP-8FJX	2
18	90305	Hose, 3/8" x 30 1/2", 6MP-8FJX	2
19	90308	Hose, 3/8" x 50", 8FJX -6MP	1
20	90313	Hose, 3/8" x 18", 8FJX-8FJX	2
21	31271	Valve, Check, Pilot	1
22	92089	Valve	1
23	30215	Hyd, Fit, Adapter, 8MB-8MJ	1
	LNC06	Nut, Nylock, 3/8"	2
	LNC05	Nut, Nylock, 5/16"	2
	LNC04	Nut, Nylock, 1/4"	2
	FW05P	Washer, Flat, 5/16", Pltd.	2


SCHEMATIC DRAWING



6.0 Cylinders


6.1 3 x 8, 1 1/4 Rod

Item	Part No.	Description	Quantity
1	30235	Nut, Hex, 1/2" UNC Grade 5	8
2	30237	Nut, Hex, 1"-14 UNS Grd 5 Phosphate]
3	30238	Cotterpin, Hamerlock, 3/16" x 1 1/2"	4
4	30239	Screw, Set, Sckt, 3/8"UNC x 1/2" Knur	1
5	30240	Fitting, Plug, 1/2"-14 NPTF Dry Seal	1
6	30241	Pin, 1" Dia, H5552	2
7	30243	Tube, Cyl., 3" x 8", H6138	1
8	30247	Rod, Tie, 1/2" x 8", H6678	4
9	30250	Piston, 3" Dia, H6880	1
10	30253	Rod, Clevis, 1 1/4", 1" Pin	1
11	30254	Rod, 1 1/4" x 8"	1
12	30256	Cap, Clevis, 3" NPTF	1
13	30257	Cap, Rod, 3" x 1 1/4" NPTF	1
14	30261	Lock, Thread, Nylon	1
15	30262	Kit, Repair, 3" Cyl.	1




6.2 3 X 10, 1 1/4 Rod

Item	Part No.	Description	Quantity
1	30235	Nut, Hex, 1/2" UNC Grade 5	8
2	30237	Nut, Hex, 1"-14 UNS Grd 5 Phosphate	1
3	30238	Cotterpin, Hamerlock, 3/16" x 1 1/2"	4
4	30239	Screw, Set, Sckt, 3/8"UNC x 1/2" Knur	1
5	30240	Fitting, Plug, 1/2"-14 NPTF Dry Seal	1
6	30241	Pin, 1" Dia, H5552	2
7	30244	Tube, Cyl., 3" x 10", H6140	1
8	30248	Rod, Tie, 1/2" x 8", H6680	4
9	30250	Piston, 3" Dia, H6880	1
10	30253	Rod, Clevis, 1 1/4", 1" Pin	1
11	30256	Cap, Clevis, 3" NPTF	1
12	30257	Cap, Rod, 3" x 1 1/4" NPTF	1
13	30260	Rod, 1 1/4" x 10"	1
14	30261	Lock, Thread, Nylon	1
15	30262	Kit, Repair, 3" Cyl.	1



6.3 3 1/2 x 13, 1 1/2 Rod

Item	Part No.	Description	Quantity
i	30236	Nut, Hex, 5/8" UNC Grade 5	8
2	30237	Nut, Hex, 1"-14 UNS Grd 5 Phosphate	1
3	30238	Cotterpin, Hamerlock, 3/16" x 1 1/2"	2
4	30240	Fitting, Plug, 1/2"-14 NPTF Dry Seal	1
5	30241	Pin, 1" Dia, H5552	1
6	30242	Rod, 1 1/2" x 13", Weldment	1
7	30245	Tube, Cyl., 3 1/2" x 13", H6203	1
8	30251	Piston, 3 1/2" Dia, H6888	1
9	30255	Rod, Tie, 5/8" x 13", Special	4
10	30258	Cap, Clevis, 3 1/2" NPTF	1
11	30259	Cap, Rod, 3 1/2" x 1 1/2" NPTF	1
12	30263	Kit, Repair, 3 1/2" Cyl.	1




7.0 Hub

7.1 Tandem Wheel

- Item	Part No. Description		Quantity			
1	30220	Cap, Dust	1			
2	30221	Cotterpin, 3/16" x 1 3/4"	1			
3	30222	Nut, Slotted, 1 1/4"	1			
4	30223	Washer, Flat, 1" SAE	1			
5	30226	Race, Inner	1			
6	30228	Seal, Grease	1			
7	30229	Hub, 8-Bolt	1			
8	91111	Bearing, Outer	1			
9	91131	Race, Outer	1			
10	91133	Bearing, Inner	1			


Note: Wheel bearings should be repacked yearly.



7.2 Castor Wheel

Item	Part No.	Description	Quantity
1	30232	Race	2
2	91073	Hub, 4-Bolt	1
3	91093	Seal, Grease	2
4	91113	Bearing	2

Note: Wheel bearings should be repacked yearly.




8.0 Electrical

8.1 Electrical Schematic

Item	Part No.	Description	Quantity
1	40102	Box, Control, 700BM (1997)	1
2	92078	Harness, Extension, 5&7BM	1
3	92089	Valve	0


Note: Black wire from control box to tractor ground

Red wire from control box to tractor ignition accessory.



8.2 Control Box and Wiring Harness

Item	Part No.	Description	Quantity		
1	92103	Electrical, Plug Male	1		
2	92105	Electrical, Plug Female	1		
3	92107	Switch, On/Off	1		
4	92136	Switch, Toggle	1		
5	92138	Fuse, Body	1		
6	92139	Fuse, Cap	1		
7	92140	Fuse, 20 Amp	1		
8	92146	Enclosure, Plastic	1		
9	92157	Pin, Male Plug	2		
10	92158	Socket, Female Plug	2		
11	92159	Wedge, Locking, Male, Plug	1		
12	92160	Wedge, Locking, Female Plug	1		
13	92164	Screw, Tapping, #4 x 1/4	4		
14	92221	Plate, Face, Box, Control	1		
15		Wiring, Box, Control, 6 ft	1		



9.0 Specifications

Weight	Approximately 4,500 lbs (2,065 kg)
Total Length	41'7"
Bed Length	37"
Total Width	8'
Bed Width	2'
Total Height	9'2"
Bed Height	3'3'''
Ground Clearance	13 1/2"
Maximum Capacity	7 – 5 Ft. Bales
Chain & Sprocket	Heavy Duty ASA 2062, 1 1/2 Pitch
Tires	Goodyear, 11L-15FI, 12 Ply
	Farm Highway Service
Undercarriage	2 – 2 wheel oscillating tandems
Horsepower Required	60 Horsepower
Hydraulic Outlets	2
Hydraulic Pressure	2500 psi.(17240 kPa)

1450

Bumper BALE

BOLL OF MATERIAL REPORT

12.5,77		186										=====
1111 0		DESCRIPTION	DESCRIPTION	RUANTET:	7 14 7 E	o n ₹		prones	T ERROR D	,taku	AATU INTIS	·
	sag. ITE	T NUNBER										-
		KIT, KUMPER. BALE) Bale,			100,	200					====
517	9 6-32990]	46998	ROTHER, BALE	1.089	ΞĠ	ч		1	9.99	8.09	1,00 EA	
31	2 1-988291	E3611	TUBE, FUMPER, BALE	1,820	ΞQ	R		1	6.66	2.53	1,60 24	
5.5	r 2-356861	MAG23758158HSR	2.375 OD X .158 HSS ROLND	6.985	ΣŢ	된		1	\$3,58	3,88	53 .5 8 l.	
2.1	1-0000008	53613	TUPE, EUNPER. BALE	8.000	E 3	Ķ		2	3,88	2,23	8.88 EA	
			2.5 x 2.5 .188 HSS 89UARE	9,360	/WT	N		i	12,00	3.05	15,83 IN	
	: 1-003983		BUSSET, BUTPER, BALE	2,598		N		2	5,38	2.98	2.82 EA	
			1/4 X 6 FLOT BAR	5.128	/241	8		1	5,88	2,39	1,3 3 IN	
							EACH LEN	5Th (2)	.ED E 69.	,775		
F 1	. 1-328384	14008P	1/8 EMO NUT PLATED	2.000	PERZO	N		Ē	3,89	2.00	2,63 53	
50	<u> </u>	49513	7-4 * =	ର, ଅଧିକ	£a	4		2	2,88	2.28	2.00 CA	
Ē.,	: 1- 20 0031	EF167	11.90,0370 5R.8 413	2.500	ΞA	1 ;		<u>•</u>	0.33	0,03	1.27 EA	
			3 Y 2 X .188 703748		ZCWT	Ŋ		•	16.89	6.20	13,73 14	
	- 358582 : 3		PERTENTALNING BUMPER DALE	2,863	£A	<u> 13</u>		4	€,2€	5.63	1,88 88	
		EAW8375899878	3/8 / 2 FLAT BAR	3.7 20	/C#1).		į	8.13	2,13	52.69 (3	
	u 0-3≾2 05 3		JERLY, 5-5 % 5 % % 5 156	3,358	28	÷		3	2,15	3,63	2.36 24	
	2-000064		5/8 UNI LICKHUT	4.PSB	985.0	, K		4	8. 28	0.83	4.88 54	

i shi, of datemial items primites,

2070

A210.00 Retail