

Pre-Delivery Inspection Checklist RCH™ 415

Deale	ership:			
Technician:				
	Customer Name:			
				aa. b.
Mode	Model:			
Seria	Serial #:			
Estimated Setup Time: 2 hours				9
~ <- 4ns.				
Safety:				
	Operator's manual located in the desig holder. Ensure all safety decals are in place and Safety locks are functional and in place	nd legible. ce.	•	pping bolts on mower hitch pivot point. and nuts. (Fig 3).
	Safety chain inspection (refer to manual Safety lights and slow maying vehicles	UDUIC	ational Check:	
	Safety lights and slow moving vehicle s functional and visible.	sign are	□ Cvcle all hvdra	aulic functions - Wing fold, deckraise and
		÷		wing and gradient steering. Install all
	heck List: lefer to operator's manual for instructions).		transport locks after testing. Run mower. Disengage and engage wing blade pans. Use caution when running machine, ensure others are away	
	Wash the unit, removing all road debris and other material).		from machine	
	Check for aesthetic defects and shippir replace damaged items or touch up pa		omer Review:	
	required.	_		'
	Check wheel bolts, as per operator mar specifications.	Г	 Review with the customer the understanding and operation of the machine. Review with the customer the safety section of the 	
	Check tire pressure and adjust as requi	ured.	operator's mai	•
	Verify machine has been greased as permanual specifications.	•	ments:	
	Remove shipping brackets (long yellow	w ones	Nems:	
	located on sides of swing hitch) discard			
	along with applicable hardware. (Fig 1) Remove PTO from storage hanger and i			
_	machine (Fig 2).	Ilistan onto		
	Oil reservoir level is correct as per operator			
П	manual specifications.			
	Inspect machine for any loose or missir hardware.	ng		
Com	npleted:	Signature:		Date:





Fig 1.



Fig 2.



Fig 3.

